




An ISO 9001 : 2015 Company











Oasis Engineering & Fabrication Works an

ISO: 9001: 2015 certified company, incepted with a mission of catering the industry as a solution provider. We aim to become a one stop shop for all the industry needs.

Our motto is "Providing key solutions" and our goal is to become a leading Industry service provider.

We provide a range of products and services to our clients, which includes the following:

- Machining & Fabrication services.
- Design & Engineering Services.

Moreover in a short span of time, we have become a prominent manufacturer, supplier and exporter of a comprehensive collection of Measuring Instruments and Industrial Valves. Our products are widely appreciated by our customers due to their durability, accuracy,low maintenance and wear resistance.

Having an in-house manufacturing facility combined with our highly skilled / trained staff of engineers and production personnel,we are capable of providing our customers with quality products that can be customized as per their requirements and demands. We also have a team of expert professionals, which keeps a regular touch with customers to understand their demands and requirements in a better way. Further, our team also helps us in maintaining cordial relations with customers by providing them customized solutions as per their requirement.

As a total service provider, we offer complete after sales service for our product range. Some of our satisfied customers are *Proserv FZE*, *Accudyne Industries FZE*, *Check Point Pumps Systems*.

Oasis aims to be the leading service provider, delivering quality manufacturing, Design & Engineering services to the industry.



RANGE OF PRODUCTS

Calibration Pots

- ► High Accuracy & Competitive cost
- We construct as per customer requirement and supply with screwed or flanged connection.
- ► Borosilicate Glass fully stressed relived

Specifications as per clients requirement **Connection size** 1.5NB to 50NB flanged type/screwed **Capacity-20ml to 40,000ml**

Sight Glass

- It contains two toughened glassess mounted opposite to each other
- ► The double window type sight glass is very easy to replace glass without dismantling the whole side glass assembly from process line

Design Temperature: 210°C with PTFE sealing **Size**: **1.5"** to 6"

Rotameter

▶ Accuracy: +/- 1.5% of FSA

Range ability:10:1

► Repeatability: +/- 0.25 % of SSA

► Temperature Rating : -50 to 120°c

End connection: As per client's requirements

Wetted part: As per Client's

requirement

Level Switch

- ► Installation: Normally Side & Top mounted for special application
- ► Conduit connection :1/2" BSP (F) with 1/2"BSP (M)
- MOC of Floats: SS304,SS316,PP SS304 with PVDF coated
- Process connection : Flanged or screwed
- Switch type : Micro Switch (SPOT or DPDT.)

Rating: SA/250V AC
Accuracy: + - 2mm
Repeatability + - 1 mm

Y-Type Strainer

- Integrally Cast Housing
- Bolted Cover c/w Drain Plug.
- Special Gasket, Special Screen
- D.P. Tappings/Gauge.
- ► Flanged Drains / Drain Valves.
- Special Finish / Linings
- ► ASME B16.5 Flange Dimensions.
- ► EN 10204 / NACE Certification.

Size: 1/2"" to 12" nominal bore

We also manufacture: T Type, Basket Type and Customized fabricated strainer as per enquiry.

For complete range of products, please visit: www.oasis-eng.com Sales Enquiry : sales@oasis-eng.com



RANGE OF PRODUCTS











Butterfly Valve

- Butterfly Valve provides positive isolation in a wide spectrum of services in Oil and Gas, Refining, Petrochemical, Chemical industries.
- ► User friendly in nature
- ► Durable and sturdy

Material of construction :

Standard Carbon Steel, SS316, Duplex, Super Duplex as per client requirement.

Ball Valve

- These are typically quarter turn valves mounted opposite to each other
- ► Floating Ball / Trunnion Mounted
- ► Full or Reduced Bore
- ► Manual Lever, Gear or Actuator Operated
- ▶ 2 or 3 Piece Bolted Construction

Material of construction:

Standard Carbon Steel, SS316, Duplex, Super Duplex as per client requirement.

Check Valve

- Split Disc, Swing, Piston, Ball, Needle, Nozzle Types
- ► Full or Reduced Bore
- Special Seat Design Options
- Modification service available for all stock options

Material of construction :

Standard Carbon Steel, SS316, Duplex, Super Duplex as per client requirement.

Gate Valve & Globe Valve

- Gate Valve : Size: 1/2" up to 24" (DN 50 up to DN 2200)
- ► Globe Valve : ½" up to 24" (DN 15 up to DN 600)
- Globe valve & Gate Valve can be designed in a special version suitable for cryogenic service.
- ► End Connection: Screwed, Socket Weld, Flanged, Hub End, Butt-Weld

Material of construction :

Standard Carbon Steel, SS316, Duplex, Super Duplex as per client requirement.

Relief Valve

- ► Compact and Simple Design. Prevents fluid -leakage efficiently
- ► Smooth and Secure operation
- ► Long Service life
- Trim parts and adjusting spring are made of stainless steel for outstanding corrosion resistance.

Material of construction:

Carbon Steel, Stainless steel standard. We can customize as per requirement.